

## Local Display (Available for Turbine or Oval Gear Meters)

Choose the 09 Computer for local display on G2 Series Turbine Meters. Commonly used features are preprogrammed in the Standard 09 Computer Display. End-users can enable additional features by using a password available from the factory or on the Flowtechnik web site.

The 09 configuration provides a very high degree of customisation, matching customers' exact needs.



Local Display for Turbine Meter



Display With Pulse Output

### Features and benefits:

- 2 Totals (1 Resettable, 1 Cumulative).
- Flowrate display updates every 5 seconds, readout is in units/minute.
- Factory Calibration in gallons and litres.
- 2 user-defined Field Calibrations.
- Small, compact and totally self contained with an internal power supply.
- Field replaceable Lithium batteries for long life.
- Automatic on and off.

Using a password-protected configuration process can enable the additional features. Our Customer Service can provide the password and instructions to unlock and reset configuration settings. This information is also available on the Flowtechnik web site. User configuration features include:

- Totalizers / Modes Enabled (Cumulative Total, Batch 1 Total, Batch 2 Total, Flowrate Mode)
- User can change Flowrate Update Interval
- Flowrate Timebase (Minute, Hour, Day)
- Factory Calibration Curve Enabled in GAL and LTR
- Field Calibration Curve B and/or C Enabled
- Dispense/Display or K-Factor Entry Calibration
- Maximum Resolution for Field Calibration (0, 1 or 2 Decimals)

### 09 COMPUTER – SPECIFICATIONS

Std. Factory Configuration:	2 Totals (1 Resettable, 1 Cumulative); Factory Calibration in gallons and litres; 2 User Calibrations and Flowrate
Computer Electronics:	09 Computer fits all A1 and G2 meter sizes and construction. Std. Display fits GM Series Meters.
Totalizing Registers:	0 to 3 available
K-Factor Limits:	Min: .01 pulses/unit Max: 999,999 pulses/unit
Field Calibration:	Field calibrate by user. Standard Method: Dispense/Display. Six adjustable digits. Can be reconfigured to K-factor entry.
Readout Totals:	LCD with floating decimal Minimum Display = 0.01 units Maximum Display = 999,999 units (6 digits)
Input Pulse Rate:	Minimum (Pulse-in Input) = DC (0 Hz) Minimum (Coil Input) = Approximately 10 Hz Maximum = Approximately 1,000 Hz
Turbine Display:	
Internal Power Supply:	2 Lithium batteries at 3 volts each
Minimum Battery Life:	9,000 hours
Optional Power Supply:	7 to 30 VDC
Oval Gear Display:	
Internal Power Supply:	9-volt battery
Optional Power Supply:	10 to 18 VDC
Operating Temperature:	+14°F to +140°F (-10°C to +60°C)
Storage Temperature:	-40°F to +158°F (-40°C to +70°C)

ALL APPROVED