



# UK Flowtechnik

Specialists in flow metering, pumps, couplings  
and process measurement equipment

## PRODUCT DATASHEET



UK Flowtechnik Ltd  
1 Central Park  
Lenton Lane  
Nottingham  
NG7 2NR  
United Kingdom

Phone +44 (0) 11 59 01 71 11  
UK Free Phone 0800 4334 770  
Fax +44 (0) 11 59 86 88 75

[sales@ukflowtechnik.com](mailto:sales@ukflowtechnik.com)  
[www.ukflowtechnik.com](http://www.ukflowtechnik.com)

# 880 Series Flanged Sight Glasses



## Straight through with spout

Ideal for gravity feed systems, intermittent flow, liquids containing entrained air and low flow rates. This model has an integral drip lip and can be mounted in any pipeline position.


## Rotor

This model has a rotor to show you if the liquid is flowing. The indicator can be mounted in any pipeline position, and the light weight rotors will operate over a wide flow range.

## Flap

The basic model is suitable for horizontal and vertically upward flow.

## Dimensional Data



DN	15	20	25	32	40	50	65	80	100	125	150	200	250
BL N model	130	150	160	180	200	230	290	310	350	400	480	600	730
BL A model	130	130	14	/	180	220	/	260	260	/	360	460	/

## Ordering Information

880.N 2 1 50 2 3

Style	
With Graphite Seals	880.N
With PTFE Seals (only available on CS & SS models)	880.A

Body Material	
Grey Cast Iron	1
Carbon Steel	2
Stainless Steel	3

Glass Type	
Soda Lime Glass (standard, max 150°C, 16 Bar)	1
881.N Borosilicate Glass (max 40 Bar, max 250°C)	3
881.A Borosilicate Glass (max 16 Bar, max 250°C)	4

Connection Size	
1/2" (DN15)	15
3/4" (DN20)	20
1" (DN25)	25
1.1/4" (DN32) (Style N only)	32
1.1/2" (DN40)	40
2" (DN50)	50
2.1/2" (DN65) (Style N only)	65
3" (DN80)	80
4" (DN100)	100
5" (DN125) (Style N only)	125
6" (DN150)	150
8" (DN200)	200
10" (DN250) (style A only)	250

Style	
Drip Tube	1
Rotor	2
Flap	3

Flange Type	
DIN PN16	1
ANSI 150LB	2
ANSI 300LB (style N only, 40 Bar Borosilicate Glass required)	3