



Specialists in flow metering, pumps, couplings and process measurement equipment



PRODUCT DATASHEET



UK Flowtechnik Ltd 1 Central Park Lenton Lane Nottingham NG7 2NR United Kingdom Phone +44 (0) 11 59 01 71 11 UK Free Phone 0800 4334 770 Fax +44 (0) 11 59 86 88 75

> sales@ukflowtechnik.com www.ukflowtechnik.com

A1 Series Commercial Grade Meter



FLOMEC[®] A1 Series Meters are designed as self contained, battery powered units. Select the A1 Series when you need an accurate, basic meter.

Features & Benefits


- Unique package combines Turbine and LCD into a selfcontained, compact, economical meter.
- Local Display Computer features: 2 Totals (1 Resettable, 1 Cumulative); Rate of Flow and User Configuration.
- Lightweight, compact design allows for easy installation.
- Lithium battery life: 5 years
- Factory calibration in gallons and litres (can also be field calibrated to other fluids).

Technical Data

	A025	A100	A200	N025	N100		
Flow Range I/min	1-11	11-190	114-1,135	1-11	11-190		
Connection Size	1″		2″	1″			
Body Material		Aluminium	Nylon				
Rotor/Shaft/Bearing Material	Nylon/Tungsten/Ceramic (316 Strainless Steel retaining rings)						
Linearity	+/- 1.5% of Reading (A025 & N025 dependant on application as they are Pelton wheel designs)						
Max Pressure (Bar)	21 Bar			10.3 Bar			
Max Temperature (°C)	60°C						
Output	Battery powered LCD with Flow Rate & 2x totals (one with reset) in either Litres or US Gallons						

Dimensional Data

	A025	A100	A200	N025	N100
Α	63	63	114	63	63
В	51	51	76	51	51
с	102	102	152	102	102



Ordering Information

